



Technical Data Sheet

Product: Primary Pro – Pre Made Elbows

Product Codes: PPEO28 – 28mm Pre Made Elbows | PPEO35 - 35mm Pre Made Elbows

Date Issued: November 2025 **Version:** Rev 1

Product Description

Primary Pro Pre-Made Elbows are factory-formed insulation bends designed to provide a fast, clean and professional solution for insulating 90° pipework transitions. Manufactured from the same coated polyolefin thermoplastic used in Primary Pro straight insulation, these elbows ensure consistent insulation thickness, long-term durability and a high-quality finish.

Each elbow is pre-assembled, bonded and sealed during manufacture, eliminating the need for installers to create elbows on site. This significantly reduces installation time and ensures a uniform appearance across the entire insulated pipe run.

Applications

- External insulation for 90° bends on ASHP systems
 - Air source heat pump installations
 - Domestic and installations
 - Designed to integrate with Primary Pro insulation lengths
-

Features & Benefits

- Factory-made elbows for a consistent and professional finish
 - Saves time on site by removing the need for hand-cut fabrication
 - Manufactured from the same coated polyolefin thermoplastic as Primary Pro insulation
 - Durable weather-resistant and UV-stabilised outer coating
 - Maintains insulation integrity and thickness around bends
 - Pre-assembled and sealed for quick installation
 - Works with Primary Pro Bond & Seal for adjoining joints
 - Suitable for all-weather external use
 - Neat and reliable solution for system designers and installers
-

Technical Data

Property	PPEO28	PPEO35
Application	90° insulation elbow for 28 mm systems	90° insulation elbow for 35 mm systems
Material	Coated polyolefin thermoplastic	Coated polyolefin thermoplastic
Colour	Black	Black
UV Resistance	Yes	Yes
Water Absorption		
Temperature Resistance	-40°C to +100°C	-40°C to +100°C
Installation Joint Sealant	Primary Pro Bond & Seal	Primary Pro Bond & Seal
Product Supplied	Pre-formed, bonded and sealed elbow	Pre-formed, bonded and sealed elbow

Installation

- Install using the same method as Primary Pro straight insulation
- Position the pre-made elbow onto the insulated pipework
- Apply Primary Pro Bond & Seal to all adjoining joints and transitions
- Ensure the elbow is correctly aligned and fully seated
- Remove any excess sealant for a clean finish
- Allow the sealant to cure according to manufacturer guidance

Storage & Handling

Store in a cool, dry place away from direct sunlight.

Avoid crushing or compressing the pre-formed shapes.

Inspect elbows prior to installation to ensure no damage or deformation.

Health & Safety

Non-hazardous under normal conditions of use.

Follow standard PPE guidance when handling or preparing adjoining insulation.

Contact

SMARTOVATIONS LTD

176-178 Pontefract Road

Cudworth

Barnsley

S72 8BE

Telephone: 01433 440290

Email Address: info@primarypro.co.uk

Website: www.primarypro.co.uk

Legal Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.